



## Geberit Duofix frame for wall-hung WC, 112 cm, with Delta concealed cistern 12 cm, flush plate Delta21



### Application purposes

- For drywall construction
- For installation in part- or room-height prewall installations
- For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For floor constructions 0–20 cm

### Characteristics

- Self-supporting frame, powder-coated
- Frame top open
- Frame with  $\varnothing$  9 mm drilling holes for fastening in wood frame construction
- Frame with holes to receive Geberit Duofix wall anchors for elements with frame top open
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- Galvanized feet
- Feet adjustable 0–20 cm
- Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- Connection bend can be mounted without tools
- Concealed cistern with front actuation
- Concealed cistern fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II

- Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- Equipped with conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- With fastening option for electrical connection

### Technical data

|                                      |                 |
|--------------------------------------|-----------------|
| Maximum operating temperature, water | 25 °C           |
| Flush volume, factory setting        | 5.8 and 3 l     |
| Flush volume large, adjustment range | 4.5 / 6 / 7.5 l |
| Flush volume small, adjustment range | 3-4 l           |

### Scope of delivery

- Angle stop valve R 1/2", with adaptor ring
- Protection box for service opening, made of polystyrene foam
- 2 distance bolts
- Flush plate Delta21
- 2 wall anchors
- Connection set for WC,  $\varnothing$  90 mm
- Connection bend 90° made of PE-HD,  $\varnothing$  90 mm
- Adaptor socket made of PE-HD,  $\varnothing$  90 / 110 mm
- 2 protection plugs
- Cup for flush volume reduction 4.0 / 2.6 l
- Crossbar for panelling support
- 2 threaded rods M12
- Fastening material

| Art. no.     | Surface / colour    |
|--------------|---------------------|
| 458.118.21.1 | gloss chrome-plated |

### Accessories

- Geberit set of support brackets for WC ceramic appliances with small contact surfaces



- Any boarding must be fixed tight up against the face of the Duofix frame and screwed directly to the frame
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first
- Flush valve features settings to enable either a 6 l and 3 l flush or a 4.5 l and 3 l flush. Note: must be used with pans designed for low volume flush